


Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

ATLANTIC SURF VINYL FLOORING 1590

SKU: 1590



Atlantic Surf Vinyl Flooring from the Classic Mystique PUR retains the uncomplicated, clean architectural feel of subtle neutrals, but now with added warmer tones for a perfectly balanced combination. Available in harmonious colours, Classic Mystique PUR has a tonal non-directional appearance, featuring a duotone chip decoration with marbled tonal highlight chips.

Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

- [Overview](#)
- [Downloadable Assets](#)
- [BOQ Specification](#)
- [Technical Product Compliance](#)
- [Comprehensive Specification](#)

Overview

Polyflor Homogeneous PUR ranges demonstrate outstanding durability and abrasion resistance. Classic Mystique PUR achieves EN ISO 10581 Type I Binder Content.

Following an individual assessment from BRE Global, Classic Mystique PUR achieves an A+ rating in major sectors such as health, education and retail (ENP472).

Classic Mystique PUR is 100% recyclable and contains 25% recycled material. Ideally suited for heavy traffic areas, Classic Mystique PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.

Downloadable Assets

- [BoQ Specification](#)
- [Comprehensive Specification](#)

BoQ Specification

Supply and install 2.00mm x 2.00m Polyflor Classic PUR homogeneous monolayer vinyl sheeting with PUR polyurethane reinforcement cross linked and UV cured surface treatment, manufactured in accordance with ISO 10581 (EN 649) and installed with Polyflor recommended adhesive which has been spread using an A2 notched trowel on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including all cutting and waste, rolling the installed sheeting in both directions with a 68kg three-sectional roller immediately after it has been laid into the adhesive, joints must be butted, U-shape grooved and heat welded using Polyflor's matching welding rod ensuring that the welding rod bonds to more than 2/3rds of the sheet in thickness, available from Polyflor (011) 609 3500.

- **Colour:** Atlantic Surf

Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

- **Code:** 1590
- **Weld Rod:** 1590

Technical Product Compliance

- Full conformance with the requirements of ISO 10581/EN 649
- Flexible pvc sheet and tile flooring in 2mm thickness
- Use area classification 23/34/43 as defined in ISO 10874/EN 685
- Fully tested to EN 13501-1 in respect of flamespread
- For slip resistance, classified DS to EN 13893
- Classified Type I within ISO 10581 re Binder Content
- BRE Global A+ rating ENP 472* in major use areas such as education and healthcare
- Tested to international standards for low VOC emissions

Comprehensive Specification

Supply and install Polyflor Classic Mystique PUR flexible PVC sheet flooring in 2.0mm thickness, homogeneous and monolayer in construction, and shall be manufactured by calendaring and pressing, to ensure a dense, smooth surface and non-directional design. the flooring shall incorporate a specially formulated polyurethane reinforcement, to significantly reduce maintenance costs, the flooring material shall conform fully with the requirements of EN 649/EN ISO 10581, the flooring must have a Use Area Classification of 23/34/43, as defined in EN 685/EN ISO 10874, in respect of flame spread, the flooring shall have been fully tested to EN 13501-1 and certified as having Class Bfl-S1, the flooring shall have been fully tested to ASTM E648 and certified as having passed with a Class 1 rating, making it suitable for use in institutional, commercial and public buildings. The flooring shall also have been tested to ASTM E662 and have a result of <450, with regard to EN 13893 for slip resistance, the flooring shall be classified DS, making it suitable for use in areas which are predominantly dry, but with occasional spillage, with regards to EN ISO 10581 the product shall be classified Type I, the flooring must possess a valid Agrément certificate when laid in accordance with the instructions of Polyflor, with coved skirtings and welded joints, this product does not accumulate static charges above 2kV and is classified as 'antistatic' when tested to EN 1815. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges, the flooring must be available in 2.0 metre width, to minimise the number of joints, in respect of light fastness, the flooring shall have been fully tested to ISO 105-B02 Method 3 and obtain ≥ 6

- **Colour:** Atlantic Surf
- **Code:** 1590
- **Weld Rod:** 1590

DO YOU HAVE QUESTIONS ABOUT VINYL FLOORING?

[CONTACT US](#)



Let us help you select the right vinyl products to ensure successful flooring and wall solutions.