

Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

BEIGE VARNISHED WOOD VINYL FLOORING 4069

SKU: 4069



Beige Varnished Wood Vinyl Flooring from the Expona Commercial Wood PUR range is a collection of luxury vinyl tiles, replicating the beauty of natural timber for use in heavy commercial areas.

Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

- [Overview](#)
- [Downloadable Assets](#)
- [BOQ Specification](#)
- [Technical Product Compliance](#)
- [Comprehensive Specification](#)

Overview

Expona Commercial PUR - Wood Collection - flooring design for heavy commercial areas

Developed using exclusive and protected designs, the highest technical quality and environmental standards are met with a range of multi-formatted tiles and planks, mirroring the beauty of natural materials and creative effects.

Suitable for use within all heavy commercial and residential situations

Creative inlay accessories are readily available to create individual floor designs

Bespoke cut designs can be produced on demand to meet each unique requirement

BRE Global A+ Rated Product (Certificate No: ENP 429) in major use areas *

Featuring a polyurethane reinforcement (PUR) to assist reduce ongoing maintenance costs

Indoor Air Comfort GOLD - Low VOC Emissions

Downloadable Assets

- [BoQ Specification](#)
- [Comprehensive Specification](#)

BoQ Specification

Supply and install Expona Commercial PUR, flexible PVC tile and plank flooring in 2.5mm thickness, having the following laminated construction: circa 0.55mm clear PVC wear layer, circa 0.07mm print film layer and circa 1.88mm backing ply with PUR polyurethane reinforcement cross linked and UV cured surface treatment, manufactured in accordance with ISO 10582 (EN 649) and installed with a Polyflor recommended adhesive which has been spread using an A2 notched trowel on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including cutting and waste, rolling the installed

Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

planks/tiles in both directions with a 68kg three-sectional roller immediately after it has been laid into the adhesive, joints must be butted joined, available from Polyflor (011) 609 3500.

- **Colour:** Beige Varnished Wood
- **Code:** 4069

Technical Product Compliance

- Expona Commercial PUR - Wood Collection - flooring design for commercial areas
- A wide collection of authentic wood designs incorporating a variety of realistic surface textures
- Suitable for use within all heavy commercial and residential situations
- BRE Global A+ Rated Product (Certificate No: ENP 429) in major use areas *
- Featuring a polyurethane reinforcement to reduce maintenance costs
- Indoor Air Comfort GOLD - Very low VOC Emissions
- Contains average 40% recycled content
- EPD available upon request

Comprehensive Specification

Supply and install Expona Commercial PUR, flexible PVC tile and plank flooring in 2.5mm thickness, having the following laminated construction: circa 0.55mm clear PVC wear layer, circa 0.07mm print film layer and circa 1.88mm backing ply, the flooring shall feature a high quality, cross-linked polyurethane reinforcement to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.

In accordance with EN ISO 10582, the in-use classification must be at least 23/33/42, as defined in EN ISO 10874: i.e., domestic areas with heavy use; commercial areas with heavy use, in respect of flame spread, the flooring shall have been fully tested to EN 13501-1 and certified as having Class B -S1, achieving the criteria EN ISO 9239-1 $\geq 8\text{kw/m}^2$ and the mandatory requirement of EN ISO 11925-2 pass. The flooring shall have been fully tested to ASTM E648 by an independent test house and classified as Class 1 rating, making it suitable for use in institutional, commercial and public buildings, with regard to EN 13893 for slip resistance, the flooring shall be classified DS, making it suitable for use in areas which are predominantly dry, when tested to DIN 51130, the flooring achieves an R10 slip rating, for flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges, the product's weight should not be more than 4,290g/m², in respect of light fastness, the flooring shall have been fully tested to ISO 105-B02 Method 3 as having a pass to ≥ 6

- **Colour:** Beige Varnished Wood
- **Code:** 4069

DO YOU HAVE QUESTIONS ABOUT VINYL FLOORING?

[CONTACT US](#)

Let us help you select the right vinyl products to ensure successful flooring and wall solutions.

