

SPECIFICATION SHEET
NO:

PSA
07

DESCRIPTION:

Standard XL

DATE:

FEB
2023

ARCHITECTURAL SPECIFICATION / BOQ

Supply and install 2.00mm x 2.00m Polyflor Standard XL homogeneous monolayer uncoated vinyl sheeting manufactured in accordance with ISO 10581 (EN 649) and installed with Polyflor recommended adhesive which has been spread using an A2 notched trowel on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including all cutting and waste, rolling the installed sheeting in both directions with a 68kg three-sectional roller immediately after it has been laid into the adhesive, joints must be butted, U-shape grooved and heat welded using Polyflor's matching welding rod ensuring that the welding rod bonds to more than 2/3rds of the sheet in thickness, available from Polyflor (011) 609 3500.

Colour:

Code:

Welding Rod:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07