

SPECIFICATION SHEET
NO:

PSA
103

DESCRIPTION:

EXPONA SIMPLAY PUR

DATE:

AUG
2023

ARCHITECTURAL SPECIFICATION / BOQ

Supply and install flexible Expona Simplay PUR PVC tile and plank flooring in 5.0mm thickness having the following laminated construction: circa 0.70mm clear PVC wear layer, circa 0.07 mm print film layer and circa 4.23mm backing ply layers, the flooring shall feature a high quality, cross-linked polyurethane reinforcement to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention, in accordance with EN 649/EN ISO 10582 and installed on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including cutting and waste, available from Polyflor (011) 609 3500.

Colour:

Code:

Welding Rod:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07