

SPECIFICATION SHEET  
NO:

PSA  
151

DESCRIPTION:

EXPONA FLOW PUR

DATE: APRIL  
2023

## ARCHITECTURAL SPECIFICATION / BOQ

Supply and install 2mm x 2m Polyflor Expona Flow PUR heterogeneous laminated construction vinyl sheeting with PUR polyurethane reinforcement cross linked and UV cured surface treatment, manufactured in accordance with ISO 10582 (EN 649) and installed with a Polyflor recommended adhesive which has been spread using an A2 notched trowel on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including all site formed skirtings (to architect's specifications) installed with PC20 Cove Former and CS48 Capping Strip, including cutting and waste, rolling the installed sheeting in both directions with a 68kg three-sectional roller immediately after it has been laid into the adhesive, joints must be butted, U-shape grooved and heat welded using Polyflor's matching welding rod ensuring that the welding rod bonds to more than 2/3rds of the sheet in thickness, available from Polyflor (011) 609 3500.

Colour:

Code:

Welding Rod:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: [marketing@polyflor.co.za](mailto:marketing@polyflor.co.za) | [www.polyflor.co.za](http://www.polyflor.co.za)  
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07