

SPECIFICATION SHEET
NO:

PSA
210

DESCRIPTION:

EXPONA ENCORE RIGID
LOC PUR

DATE:

AUG
2023

ARCHITECTURAL SPECIFICATION / BOQ

Supply and install Expona EnCore Rigid Loc rigid interlocking vinyl floor tile, having the following laminated construction: circa 0.55mm clear PVC wear layer, circa 0.07mm print film layer and circa 5mm rigid layer and 1mm IXPE acoustic foam layer, with a high quality, cross-linked polyurethane reinforcement to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention, in accordance with EN 16511, and installed on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including cutting and waste, available from Polyflor (011) 609 3500.

Colour:

Code:

Welding Rod:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07