

SPECIFICATION SHEET  
NO:

PSA  
32

DESCRIPTION:

EXPONA DESIGN PUR

DATE:

AUG  
2023

## ARCHITECTURAL SPECIFICATION / BOQ

Supply and install install Expona Design PUR, flexible PVC tile and plank flooring in 3.0mm thickness, having the following laminated construction: circa 0.7mm clear PVC wear layer, circa 0.07mm print film layer, and circa 2.23mm backing ply with PUR polyurethane reinforcement cross linked and UV cured surface treatment, manufactured in accordance with ISO 10582 (EN 649) and installed with a Polyflor recommended adhesive which has been spread using an A2 notched trowel on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including cutting and waste, rolling the installed planks/tiles in both directions with a 68kg three-sectional roller immediately after it has been laid into the adhesive, joints must be butted joined, available from Polyflor (011) 609 3500.

Colour:

Code:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: [marketing@polyflor.co.za](mailto:marketing@polyflor.co.za) | [www.polyflor.co.za](http://www.polyflor.co.za)  
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07