

SPECIFICATION SHEET
NO:

PSA
181

DESCRIPTION:

CAMARO LOC PUR

DATE:

AUG
2023

ARCHITECTURAL SPECIFICATION / BOQ

Supply and install Camaro Loc PUR flexible PVC interlocking tile and plank flooring in 4.0mm thickness, having the following laminated construction: circa 0.3mm clear PVC wear layer, circa 0.07mm print film layer, and circa 3.63mm backing ply, with a high quality, cross-linked polyurethane coating to provide superior cleaning benefits, in accordance with EN ISO 10582 (EN 649) and installed on a previously prepared Class 1 subfloor in accordance with SANS 10070, using a Polyflor recommended self-leveller and moisture barrier when required, including cutting and waste, available from Polyflor (011) 609 3500.

Colour:

Code:

Welding Rod:

SPECIALIST FLOORING & WALL PROTECTION PARTNER

Tel: 011 609 3500 | Email: marketing@polyflor.co.za | www.polyflor.co.za
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polyflor South Africa. Company Registration 2004/012256/07