

SaarFloor Noppe Stud Tile

PRODUCT SPECIFICATION

Key Features

- > Low-profile stud tile in 3mm
- > Modern timeless colours
- > Durability & comfort underfoot
- > Beneficial contribution to impact sound reduction
- > Heavy commercial use



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.0mm
Total Weight	ISO 23997 (EN 430)	4200g/m ²

Tile Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Tile	500mm x 500mm	12	20	5m ²

Performance Requirements	Standard	Result
General Performance	EN 12199	Conforms
Use Area	ISO 10874 (EN 685)	23, 32, 41
Slip Resistance	EN 13893 AS 4586	Class DS R9
Reaction to Fire	EN 13501-1	Class Bfl-S1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1	<0.25mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.30%
Underfloor Heating		Suitable, max 27°C
Cigarette Resistance	EN 1399	Method A Rating >4 Method B Rating >3

Sustainability	Standard	Result
BRE Green Guide		A+ Generic
Recyclable		100%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
AgBB/ABG		Pass

Acoustic Performance**Standard****Result****Impact Sound Reduction**

ISO 10140-3

8dB

Maintenance Performance**Standard****Result****Resistance to Chemicals**

ISO 26987 (EN 423)

Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.

**Polyflor Ltd. Head Office**

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

SaarFloor Noppe Stud Tile


RANGE SHADES

GROUP 1




Black Coal 101
NCS S 8502-R

LRV 5




Anthracite 102
NCS S 8000-N

LRV 10



Steel 014
NCS S 5502-G

LRV 21




Deep Blue 191
NCS S 7020-B

LRV 7



Limestone Green 013
NCS S 5010-B70G

LRV 22



Green Baize 015
NCS S 6030-G10Y

LRV 8

GROUP 2



Mercury 129
NCS S 3005-B80G

LRV 39




Warm Red 012
NCS S 2070-Y90R

LRV 12




Orange 010
NCS S 2070-Y50R

LRV 22



Cobalt 019
NCS S 7020-R80B

LRV 7



Cool Blue 707
NCS S 5020-B

LRV 18



Sandstone 140
NCS S 3020-Y20R

LRV 34

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1